

**Address:**  
**THƯƠNG NGUYEN CO.,LTD**  
 Land parcel 59-60-70, Map No.1, Phuoc Thai Hamlet,  
 Thai Hoa Ward, Tan Uyen City, Binh Duong Province, Viet Nam.  
**HA NOI | EURO MACHINE**  
 Berlin Love Vietnam Company Limited  
 Tax id. 0315020923  
 The 2nd floor, Ciputra Club Building,  
 Ciputra Hanoi International City, Xuan Dinh Ward, Baoc Tu Liem District, Hanoi, Vietnam  
 Mail: woodwm6232@gmail.com Website: maychebiengotn.com

**SAMACH**  
**THƯƠNG NGUYEN WOODWORKING MACHINE**  
 上源 木工机械公司

**EURO MACHINE**

LEARN MORE (+84) 902 98 58 98

### CNC Band Saw - Máy cưa lọng CNC

#### CF-KL1615



Video



Model	CF-KL1615.CNC
Operating Voltage	380V x 3P
Electricity supply	380V/ 50Hz
Total power consumption	28kW
Use gas	12mm
Cable	6mm <sup>2</sup>
Number of vacuum outlets	8" x 1
Installation dimensions	6000l x 3900W x 2020H
Machine weight	3.8T

### CNC Compound Machining Center Máy đánh mộng CNC đa năng

#### RJR5013A



Video



Model	RJR5013A
X axis effective work stroke (length)	5000 mm
Y axis effective work stroke (width)	100 mm
Z axis effective work stroke (height)	70 mm
B axis (worktable)	± 90°
Bridges of clamps	6 pcs
Tool quantity	4*4 pcs
Max work speed	20 m/min
Spindle speed	12000 rpm/ 18 rpm
Motor power	43kW
Control system	Taiwan LNC

### Five-axis Machining Center | CNC Trung Tâm 5 Trục

#### RJR-1218A



Video



Model	RJR-1218A
X axis effective work stroke	700 mm
Y axis effective work stroke	1200 mm
Z axis effective work stroke	500 mm
Work speed	1 – 20 m/min
Return speed	50 m/min
Distance between tools	260 mm
Motor power	43kW
Control system	Taiwan LNC computer control
Dust outlet diameter	100 mm

### Multifunctional Five-axis Machining Center CNC Trung Tâm 5 Trục Đa chức năng

#### RJR-1218



Video



Model	RJR-1218
X axis effective work stroke	1500 mm
Y axis effective work stroke	1000 mm
Z axis effective work stroke	500 mm
Work area	Single are 3000mm, double area 1500mm*2
Work speed	1 – 20 m/min
Return speed	50 m/min
Distance between tools	260 mm
Motor power	45kW
Control system	Taiwan LNC computer control
Dust outlet diameter	150 mm

### Five-axis Machining Center(4 Stations) - CNC Trung Tâm 5 trục 4 bàn

#### RJR-8080



Video



Model	RJR-8080
X axis effective processing distance	800 mm
Y axis effective processing distance	800 mm
Z axis effective processing distance	500 mm
Distance between tool axis	850 mm
Total power	55kW
Max speed	30 m/min
Max working speed	15 m/min
Machine weight	7000 Kg
Processing accuracy	±0.1
Transmission	Precision heavy guide rail

### 5 Axis CNC Center RF-5AH | CNC Trung Tâm 5 Trục

#### RF-5AH



Video



Model	RF-5AH
Working stroke	3080*1900*800 mm
A/C axis stroke	A: Unlimited C: +370
Spindle power	4*9.6 kW
Spindle speed	0 – 24000 rpm
Driver	Taiwan Syntec

### Woodworking PTP Center | CNC Trung tâm

#### PTP -160H



Video



Product	Item	PTP-160H
Work stroke	X*Y*Z	1300*3300*150 mm
Spindle motor	Brand	Italy HSD
Spindle power	9kW	9kW
ATC	Automatic tool change	Automatic tool change
Type	Air cooling	Air cooling
Rotation speed	18000 rpm	18000 rpm
Drive system	Mode	Servo drive
Inverter	Brand	Sundar 5.5kW
Positioning cylinder	Front work	2 sets
Rear work zone X axis	2 sets	2 sets
Vacuum block	2 pcs + 6 bridge	2 pcs+4 bridge
Drill group	8V-4H+1S boring block	
Max. work speed	Z axis	25 m/min
Y axis		25 m/min
Z axis		10 m/min

### Smart Carton Machine | Máy làm Carton hiện đại

#### EC2300



Video



Minimum carton size	80*90*13 mm
Tool configuration	1 Horizontal + 6 Vertical
Maximum cutting width	1600 mm
Corrugated paper magazine/ library	4
Corrugated paper thickness	2 – 6.5 mm
Transportation speed	60 – 120 m/min
Stacking height	Maximum 1800 mm (pallet height is excluded)
Slacking length	Maximum 1100 mm
Cutting efficiency	4 – 8 pcs/ min
Minimum carton height	13 mm
Minimum carton width	60 mm
Machine dimension (L x W x H)	850 mm
Working table height	850 mm
Carton types	31 types in total

## Sliding Panel Saw | Máy cưa bản trượt

▶ RTJ-45X



Video



Model	RTJ-45X
Main saw blade max diameter	350 mm
Main saw shaft diameter	30 mm
Main saw motor power	5.5kW (6.5kW is Optional)
Groove saw motor power	1.1kW
Saw blade tilt range	0 – 45°



## Rear Loading CNC Panel Saw | Máy cưa ván tự động

▶ RCJ4200E-R



Video



Model	RCJ4200E-R	RCJ4500E-R
Work width	4150 mm	4450 mm
Work thickness	100 mm	100 mm
Main saw motor	15 kW	15 kW
Groove saw motor	22kW	22kW
Gripper quantity	15	15



## CNC Router Line | CNC Router định tuyến

▶ RKS-F8+9V



Video



Model	RKS-F8+9V
Work stroke	1300*2500*180 mm
Spindle motor	HQD 9.0 KW auto tool change
Drive system	Japan Yaskawa 850W servo drive
Vacuum pump	HQD 5+4 vertical
Operation system	Automatic label printer



## CNC Router

▶ RTS-4S



Video



Model	RTS-4S
Work stroke	1300 x 2800 x 50 mm
Spindle motor	HQD 6kW x 4
Drive system	NC Studio servo drive
Vacuum Pump	Domestic water cycle 7.5KW



## CNC 6 Sides Drilling Machine Máy khoan 6 mặt CNC

▶ RMZ-126A/B



Video



Model	RMZ-126A	RMZ-126B
Length of board	200-2800 mm	200-2800 mm
Width of board	50 – 1200 mm	50 – 1200 mm
Thickness of board	9 – 40 mm	9 – 40 mm
Power of main shaft	3.5kW x 2pcs	3.5kW x 2pcs
Upper vertical drill	12 pcs	12*2 units
Upper horizontal drill	X:2*2 + Y:2*2	(X:2*2 + Y:2*1) * 2
Bottom vertical drill	10 pcs	10 pcs



## CNC 6 Sides Drilling Line Hệ thống Máy CNC khoan 6 mặt kèm băng tải đưa phôi tự động

▶ RMZ-6B-Line



Video



## CNC 6 Sides Drilling Machine Máy khoan 6 mặt CNC

▶ RMZ-126A-16



Video



Model	RMZ-126A-16
Efficiency	100 – 120 pcs per hour
Length of board	200 – 2800 mm
Width of board	50 – 1200 mm
Thickness of board	12 – 40 mm
X/Y/Z Max. speed	120/80/30 mm/min
Power of main shaft	9kW + 3.5kW
Speed of main shaft	18000 rpm
Upper vertical drill	12 pcs
Upper horizontal drill	X:2*2 + Y: 2*2
Bottom vertical drill	10 pcs
Machine size (L x W x H)	5500 x 3500 x 2150 mm



## CNC Drilling and Milling Center CNC Khoan phay trung tâm

▶ KHM-608D



Video



Machine name	CNC Drilling and Milling Center
Max working length	3050 mm
Effective working width range	0 – 150 mm
Max. working thickness	60 mm
Spindle motor power	6kW
Automatic change power and type	6 pcs automatic tool change in row type

## Automatic Edge Banding Machine Máy dán cạnh tự động

▶ RFB565JC-PUR



Video



Model	RFB565JC-PUR
Panel length	≥120 mm
Panel width	≥60 mm
Panel thickness	10 – 60 mm
Edgeband thickness	0.4 – 3 mm
Total power	18kW



## J/C Shaped Edge Banding Machine Máy dán cạnh tay nắm J/C


▶ RFB-18J/18C/18JCX



Video



Model	RFB-18J/18C
Panel thickness (J shaped)	18 mm
Min. panel size (J shaped)	≥ 250 x 150 mm
Edge thickness	0.51 – 0.55 mm
PVC	Matt type
Feed speed	13 m/min




## Automatic Inclination Edge Banding Machine Máy dán cạnh nghiêng - Dán No Line

▶ RFB-756H



Video



Model	RFB-756H	RFB-756JC
Panel length	Inclined straight: >250mm Straight: ≥120mm	
Panel width	Inclined straight: >250mm Straight: ≥120mm	
Panel thickness	Inclined straight: 15-25mm Straight: 9-50mm Straight reserved: >5mm	
Edgeband thickness	Inclined straight: 0.6-1.5mm Straight: 0.4-3mm	
Total power	39kW	32.5kW